

A) Calculations:			
1. Area = (L X W)			
2. Volume = Area X avg depth x 7.5 gal/cu ft (rounded up constant)			
3. Flow rate = Volume/the required turnover rate = gpm (the min required flow rate see rules 04b6f and 05.1(f)(12))			
4. Filter Max Flow = sq ft (filter area) X gpm/sq ft (NSF filtration rate) = gpm			
5. Total Dynamic Head (TDH): the resistance to flow within the pipes-fittings, the filter, and the heater to move water; the typical pool is approx = 50 ft TDH.			
6. Pump size: based on the pump curve, according to the following: a) Min. allowable flow rate b) Max. allowable flow rate c) If pump output exceeds a), but does not exceed b); the pump is properly sized with the filter* *NOTE- a throttle valve must be installed if the max. allowable filter flow-b) is exceeded, to restrict pump capacity. A throttle valve may also be used to restrict flow to suction drains or other system components.			
To Hyperchlorinate (Whenever the combined chlorine value is over approx. 0.4 ppm): the amount of free chlorine to neutralize the combined = (4) X 10 or 4.0 ppm (free chlorine) To raise Chlorine (1 ppm/10,000 gal of pool water): add 2 oz Calcium Hypochlorite (65%); add 10.7 fl oz Sodium Hypochlorite (12%) To neutralize excess chlorine (1 ppm/10,000 gal of pool water): add 1 oz Sodium Thiiosulfate-carefully, or more chlorine will be required to off set the extra neutralizer To LOWER Cyanuric Acid, Total Dissolved Solids (TDS), or Calcium Hardness: drain a portion or all of the pool. To RAISE pH (: 2 units/10,000 gal of pool water-based upon BASE demand test/Alkalinity): add 6 oz of Sodium Carbonate (Soda Ash) To LOWER pH (: 2 units/10,000 gal of pool water, based upon ACID demand test/Alkalinity): add 12 oz Muriatic acid or 1.0 lb. Sodium Bisulfate (dry acid) To RAISE Alkalinity (10 ppm/10,000 gal of pool water): add approx. 1.5 lbs. Sodium Bicarbonate (Baking Soda) To LOWER Alkalinity (10 ppm/10,000 gal of pool water): add approx. 26 oz Muriatic acid or 2.15 lbs. Sodium Bisulfate (dry acid) To LOWER Calcium Hardness (10 ppm/10,000 gal of pool water, based upon Calcium Hardness test): add .9 lbs Calcium Chloride Dihydrate (100%) Source: National Swimming Pool Foundation			
The Ohio Administrative Code requires the operator of a public swimming pool to prohibit patrons with obvious infectious wounds from using the pool as well as anyone observed passing feces, urine, or blood. The operator is also REQUIRED TO RECORD ALL injuries and fecal accidents. In the event of suspected water borne illness contact your local health district and the Ohio Department of Health, Bureau of Environmental Health, at 614.466.1390.			
Fecal/ Blood/ Vomitus Accident Report If necessary, attach additional remarks and information			
Date	Time	Description of event	
Corrective measures			
Record contact information on a separate page for ALL patrons involved			
Injury Accident Report			
Date	Time	Victim's age [] <input type="checkbox"/> Male <input type="checkbox"/> Female	Victim(s) name/Contact information
Description of accident-injuries			
First aid administered			
Comments			